

ArmorMax Profloor Technical Data Sheet

Parameter	Flooring Specifications	Ramp Specifications
		
MODULE SIZE	ACTUAL PANEL DIMENSIONS 1.09m×1.09m×4.5cm(1.18m ²) USABLE PANEL DIMENSIONS 1.0m×1.0m(1.0 m ²)	0.45m×1.0m×4.5 cm
WEIGHT	15.8kg / panel	6.3kg / panel
COMPRESSION STRENGTH	600T/m ²	
MAX ALLOWABLE DEFLECTION	7.50cm	
COLOR	Translucent white,black or grey	
MATERIAL	PP Plastic(HDPE optional)	PP Plasic(HDPE optional)
TEMPERATURE RANGE	-4°F-113°F(-20℃-45℃)	
BURN RATING	UL94-HB (Optional)	
DESIGN FEATURES	Matte non-slip ribbed surface Overlapping/underlapping fanges enhance load spread and create a smooth surface	Female and male configuration adjoin with appropriate edge of the panels.Pairs of panels are used to create build joints.
CONNECTION SYSTEM	Preinstalled nylon cam locks;vertical locking system-no loose parts T-bar locking tool	
SHIPPING CAPACITY	Standard 40HC container: 1,200 panels /1,200 m ²	